



	A	B	C	D	E	F	G
1							
2							
3							

NOTE:

1. To avoid possible misunderstanding when specifying the dimensions of bent bolts, it is recommended that they be given in order indicated by the dimension letters in brackets above each drawings . For example, if a J - bolt is required with G: 3/8 - 24 UNF, A: 6", B: 1", C:5/8, thread length D: 1 1/2, E: 7/8, F: 1 1/4, it should be specified as a 3/8" x 6" x 1" x 5/8" x 1 1/2" x 7/8" x 1 1/4" UNF J - Bolt.

G	X	A	X	B	X	D	X	E	X	F	X	Part name
	X		X		X		X		X		X	

2. Threads may be cut or rolled; blank portion of rolled thread bolts may be slightly undersize, the nominal size of the bolt referring to the basics major diameter of the threaded portion.

<p>CUSTOMER APPROVAL AS ROLLED PART DRAWING WILL BE USED FOR FINAL INSPECTION</p>	REVISION	DATE	CHANGE OR ADDITION			
	DRAWN	<p>WESTLAND FASTENERS Ltd. P.O. BOX 1052 WINNIPEG, MANITOBA R3C 2X4 PHONE: (204) 224 - 1654 FAX: (204) 224 - 5337</p>				
	APPD					
	UNITS IMPERIAL	NAME BENT BOLT				
<p>THIS DRAWING IS THE PROPERTY OF WESTLAND FASTENERS LTD AND MAY NOT BE USED IN WHOLE OR IN PART WITHOUT AUTHORIZATION</p>	TOLERANCES UNLESS OTHERWISE SPECIFIED		MATERIAL	DWG No.	REV.	FINISH
	.XX ±.010		SCALE DO NOT SCALE		DATE	SHEET
	.XXX ±.005					
	ANGL. ± 1					